



OBLK-5T7A **OBLK-5T7A-Auto**

- MOTOR POWER 5 HP
- Flow Rate of 1st Stage 11.9 L/Mit
- Flow Rate of 2nd Stage 3.8 L/Mit
- Tank Capacity (Liter) 60 (L)
- Weight (kg) 125 kg



OBLK-3T7A **OBLK-3T7A-Auto**

- MOTOR POWER 5 HP
- Flow Rate of 1st Stage 11.9 L/Mit
- Flow Rate of 2nd Stage 2.5 L/Mit
- Tank Capacity (Liter) 40 (L)
- Weight (kg) 105 kg



OBLK-3T7A **OBLK-3T7A-mANUEL**

- MOTOR POWER 5 HP
- Flow Rate of 1st Stage 11.9 L/Mit
- Flow Rate of 2nd Stage 2.5 L/Mit
- Tank Capacity (Liter) 40 (L)
- Weight (kg) 105 kg



OYLD-257A **OBLK-257A-Auto**

- MOTOR POWER 3 HP
- Flow Rate of 1st Stage 5 L/Mit
- Flow Rate of 2nd Stage 1.5 L/Mit
- Tank Capacity (Liter) 12 (L)
- Weight (kg) 60 kg



OYLD-257M **OYLD-257M-Manuel**

- MOTOR POWER 3 HP
- Flow Rate of 1st Stage 5 L/Mit
- Flow Rate of 2nd Stage 1.5 L/Mit
- Tank Capacity (Liter) 12 (L)

- Weight (kg) 160 kg



OBLD-109M
OBLD-109M 2 HP

- MOTOR POWER 3 HP
- Flow Rate of 1st Stage 3.3 L/Mit
- Flow Rate of 2nd Stage 0.8 L/Mit
- Tank Capacity (Liter) 4 (L)
- Weight (kg) 35 kg

SPECIFICATIONS HYDRAULIC PUMP					
Specification	MODEL	OBLK-ST7		OBLK-JT7	
		Auto	Manual	Auto	Manual
Three/Single Phase Power (phase)		3 phase	3 phase	3 phase	1 phase
Motor Power (HP)		3 HP	3 HP	2 HP	1 HP
Max. Operation Pressure (kg/cm ²)		750			
Flow Rate of 1st Stage (L/min)		11.9 L/min	11.9 L/min	5 L/min	0.9 L/min
Flow Rate of 2nd Stage (L/min)		0.9 L/min	2.5 L/min	1.5 L/min	0.9 L/min
Tank capacity (L)		80 (L)	40 (L)	15 (L)	4 (L)
Weight (kg)		125kg	105kg	80kg	55kg
Body Dimension L x W x H (mm)		500x350	500x350	400x250	280x250
Auto Return Support		√	√	√	—
Operation Method		Electrical Hydraulic			

Remark:
• Maximum pressure is calculation from zero to peak in atmosphere.
• Auto return function must complete with automatic type puncher. A type is meaning auto return include, M type is meaning none-auto return.