



OHK – 2832A **OHK-2832A-Auto**

- Max. Strength Output 120 ton
- Max Punching Diameter 32 MM
- Max Punching Thickness 28 MM
- Max Throat Depth (Reach) 150 MM
- Body weight 148 KG



OHK-2832M **OHK-2832M – Manuel**

- Max Strength Output 120 ton
- Max Punching Diameter 32 MM
- Max Punching Thickness 28 MM
- Max Throat Depth (Reach) 150 MM
- Body weight 148 KG



OPD-727A **OPD-727A-Auto**

- Max Strength Output 78 ton
- Max Punching Diameter 27 MM
- Max Punching Thickness 22 MM
- Max Throat depth (Reach) 125 MM
- Body weight 87 KG



OPD-727A **OPD-727A-Manuel**

- Max Strength Output 78 ton
- Max Punching Diameter 27 MM
- Max Punching Thickness 22 MM
- Max Throat depth (Reach) 125 MM
- Body weight 87 KG



OWH-525A **OWH-525A-Auto**

- Max Strength Output 52 ton
- Max Punching Diameter 25 MM
- Max Punching Thickness 16 MM
- Max Throat depth (Reach) 110 MM

- Body weight 34 KG



OWH-525A **OWH-525A-Manuel**

- Max Strength Output 52 ton
- Max Punching Diameter 25 MM
- Max Punching Thickness 16 MM
- Max Throat depth (Reach) 110 MM
- Body weight 34 KG



OHP-423A **OHP-423A-Manuel**

- Max Strength Output 38 ton
- Max Punching Diameter 23 MM
- Max Punching Thickness 13 MM
- Max Throat depth (Reach) 60 MM
- Body weight 17 KG



OCT800-400 Puncher OCT800-400

Max. Punching Force (kN) 32000

SPECIFICATIONS HYDRAULIC PUNCHER							
MODEL / Specification	OHP-2832		ODP-727		OWH-525		OHP-423
	Auto	Manuel	Auto	Manuel	Auto	Manuel	Manuel
Max. Strength Output (kN)	100		70		52		38
Max. Punching Diameter (mm)	32		27		25		23
Max. Punching Thickness(mm)	25		22		18		19
Max. Throat Depth (Reach) (mm)	190		125		110		80
Max. Cloning Length (mm)	30		27		26		24
Max. P/Operation Pressure (kg/cm ²)	750						
Weight (kg)	148		87		54		17
Detail Dimensions		30		25		18	14
	A	32		25		25	17
	B	190		125		110	80
	C	115		75		85	45
	D	120		100		80	55
	E	M14		M12		M12	M12
Body Dimension	F	80		45		41	32
	L	18		15		13	10
	W	55		47		42	32
	H	N/A		N/A		Optional	Optional
Auxiliary Handle							
Return Mode	Auto	Manuel	Auto	Manuel	Auto	Manuel	Manuel

Remark:

- Maximum output is calculation at maximum operation pressure.
- Maximum thickness is calculation at maximum diameter and punching mild steel.
- Maximum pressure is calculation from zero to peak in atmosphere.
- Auto return function must complete with automatic type pump, is meaning auto return include, M type is meaning none-auto return.

Puncherand Pump Combined Codes List							
120 TON		70 TON		52 TON		38 TON	
Hydraulic	Puncher	Hydraulic	Puncher	Hydraulic	Puncher	Hydraulic	Puncher
OHK-2832A	OBK-577A	OPD-727A	OBK-577A	OWH-525A	OBK-577A	OHP-423M	OYLD-257M
OHK-2832M	OBK-577A	OPD-727M	OBK-577A	OWH-525M	OBK-577M	OHP-423M	OBLD-109M
OHK-2832M	OBK-577A	OPD-727M	OBK-577A	OWH-525M	OYLD-257A		
OHK-2832M	OBK-577M	OPD-727M	OBK-577M	OWH-525M	OYLD-257M		
OHK-2832A	OYLD-257A	OPD-727A	OYLD-257A	OWH-525M	OBLD-109M		
OHK-2832M	OYLD-257M	OPD-727M	OYLD-257M				