



Product Name □ Pneumatic pipe Cutting and bevelling machine

Description □ Driven by pneumatic motor, No-spark in the process of working, safe and reliable operation, It could be suitable for inflammable and dangerous working.

Power □ 0.5-2.5KW

Air Working Pressure □ 0.6-1.5Mpa

Air Consuming Flux □ 1500-2000L/min.

Features □ High speed rotation, driven by low-energy consumption electric motor, easy operation, competitive. lighter weight, minimal radial space, easy to operate. APPLICATION RANGE: They are widely used in the fields of petroleum, chemical, natural gas, power supply, construction, boiler and nuclear power, such as the project of West Gas Transporting to East China.

ON-SITE PROCESS



The field processing, groove structured, no burr, easy welding.

CONVENIENT INSTALLATION



BEACIMOTOOL POST, the split is installed in the pipeline in any position, fast and convenient

INSIDE TOOL POST, according to the pipe diameter, pipe deformation ellipse machining.



Metric Standard, complete groove inner wall of pipeline, the short section wall boring. Working Range □ O-D.n

Preferable British Standard (pipe diameter 1/2"-1 1/2"). Hydraulic, NC model and Working F

Preferable capacity and model selection (pipe diameter 1/2"-1 1/2"), hydraulic, NC model and Working F